






No.	Part Name	Material
1	Body	DI/CF8/CF8M/CF3M/WCB
2	Seat	EPDM/NBR/VITON/PTFE
3	Disc	DI/CF8/CF8M/CF3M/C95400/2205/2507
4	Shaft	SS420
5	Long Bushing	FRP
6	Short Bushing	FRP
7	O-Ring	NBR
8	U-Card	SS430
9	Snap Ring	SS304

Lug-Type Backrest-Seated Butterfly Valve DN40-DN300

DN mm	INCH in	L±2	A±1	B±1	H	F	ØZ	ISO 5211				PN10		PN16		PN25		150LB	
								Actuator Flange	ØK	ØE	n1-Ød1	ØC	n-M	ØC	n-M	ØC	n-M	ØC	n-M
40	1.5	33	123	65	11	11X11	12.60	F05	65	50	4-Ø7	110	4-M16	110	4-M16	110	4-M16	98.6	4-(¹ / ₂ -13UNC-2B)
50	2	43	129	69	11.5	11X11	12.60	F05	65	50	4-Ø7	125	4-M16	125	4-M16	125	4-M16	120.6	4-(⁵ / ₈ -11UNC-2B)
65	2.5	46	137	80	15	11X11	12.60	F05	65	50	4-Ø7	145	4-M16	145	4-M16	145	8-M16	139.7	4-(⁵ / ₈ -11UNC-2B)
80	3	46	144	95	15	11X11	12.60	F05	65	50	4-Ø7	160	8-M16	160	8-M16	160	8-M16	152.4	4-(⁵ / ₈ -11UNC-2B)
100	4	52	163	109	15	11X11	15.77	F07	90	70	4-Ø10	180	8-M16	180	8-M16	190	8-M20	190.5	8-(⁵ / ₈ -11UNC-2B)
125	5	56	179	125	19	14X14	18.92	F07	90	70	4-Ø10	210	8-M16	210	8-M16	220	8-M24	215.9	8-(³ / ₄ -10UNC-2B)
150	6	56	198	137	19	14X14	18.92	F07	90	70	4-Ø10	240	8-M20	240	8-M20	250	8-M24	241.3	8-(³ / ₄ -10UNC-2B)
200	8	60	237	173	20	17X17	22.10	F10	125	102	4-Ø12	295	8-M20	295	12-M20	310	12-M24	298.4	8-(³ / ₄ -10UNC-2B)
250	10	68	281	206	24	22X22	28.45	F10	125	102	4-Ø12	350	12-M20	355	12-M24	370	12-M27	362.0	12-(⁷ / ₈ -9UNC-2B)
300	12	78	318	244	26	22X22	31.60	F10	125	102	4-Ø12	400	12-M20	410	12-M24	430	16-M27	431.8	12-(⁷ / ₈ -9UNC-2B)