




Manual Lever U-Type Backrest-Seated Butterfly Valve DN50-DN300

DN mm	INCH in	L±2	A±1	B±1	F	ØZ	L1	H	ISO 5211				PN10		PN16		150LB	
									Actuator Flange	ØK	ØE	n1-Ød1	ØC	n-Ød	ØC	n-Ød	ØC	n-Ød
50	2	43	155	82	11X11	12.60	189	76	F05	65	50	4-Ø7	125	4-Ø19	125	4-Ø19	120.6	4-Ø19.1
65	2.5	46	165	92	11X11	12.60	189	76	F05	65	50	4-Ø7	145	4-Ø19	145	4-Ø19	139.7	4-Ø19.1
80	3	46	172	100	11X11	12.60	189	76	F05	65	50	4-Ø7	160	8-Ø19	160	8-Ø19	152.4	4-Ø19.1
100	4	52	188	110	11X11	15.77	250	84	F07	90	70	4-Ø10	180	8-Ø19	180	8-Ø19	190.5	8-Ø19.1
125	5	56	209	125	14X14	18.92	250	84	F07	90	70	4-Ø10	210	8-Ø19	210	8-Ø19	215.9	8-Ø22.4
150	6	56	227	142	14X14	18.92	250	84	F07	90	70	4-Ø10	240	8-Ø23	240	8-Ø23	241.3	8-Ø22.4