




Manual Lever Wafer-Type Backrest-Seated Butterfly Valve DN40-DN150

DN	INCH	L±2	A±1	B±1	F	ØZ	L1	H	ISO 5211				PN10		PN16		150LB		10K	
									Actuator Flange	ØK	ØE	n1-Ød1	ØC	n-Ød	ØC	n-Ød	ØC	n-Ød	ØC	n-Ød
40	1.5	33	121	65	11X11	12.60	189	76	F05	65	50	4-Ø7	110	4-Ø19	110	4-Ø19	98.6	4-Ø15.9	105	4-Ø19
50	2	43	141	71	11X11	12.60	189	76	F05	65	50	4-Ø7	125	4-Ø19	125	4-Ø19	120.6	4-Ø19.1	120	4-Ø19
65	2.5	46	150	85	11X11	12.60	189	76	F05	65	50	4-Ø7	145	4-Ø19	145	4-Ø19	139.7	4-Ø19.1	140	4-Ø19
80	3	46	158	100	11X11	12.60	189	76	F05	65	50	4-Ø7	160	8-Ø19	160	8-Ø19	152.4	4-Ø19.1	150	8-Ø19
100	4	52	176	114	11X11	15.77	250	84	F07	90	70	4-Ø10	180	8-Ø19	180	8-Ø19	190.5	8-Ø19.1	175	8-Ø19
125	5	56	190	128	14X14	18.92	250	84	F07	90	70	4-Ø10	210	8-Ø19	210	8-Ø19	215.9	8-Ø22.4	210	8-Ø23
150	6	56	211	139	14X14	18.92	250	84	F07	90	70	4-Ø10	240	8-Ø23	240	8-Ø23	241.3	8-Ø22.4	240	8-Ø23