




No.	Part Name	Material
1	Hex Nut	SS304
2	Gasket	PTFE/R-PTFE
3	Main Body	WCB/CF8/CF3M
4	Ball	SS304/SS316L
5	Seat	PTFE/R-PTFE
6	Bolt	SS304
7	Bonnet	WCB/CF8/CF3M
8	Thrust Washer	R-PTFE
9	O-Ring	FKM
10	Stem	SS304/SS316L
11	Packing	PTFE/R-PTFE
12	Packing Gland	WCB/CF8

Three-Piece Thread Ball Valve DN15-DN100

DN	INCH	L±2	D	H	H1	P	ISO 5211	
mm	in						Actuator Flange	Pitch Circle Diameter
15	1/2	75	G NPT BSPT	46	9	9X9	F03 F05	Ø36 Ø50
20	3/4	80		47.5	9	9X9	F03 F05	Ø36 Ø50
25	1	90		60	11	11X11	F04 F05	Ø42 Ø50
32	1¼	110		64	11	11X11	F04 F05	Ø42 Ø50
40	1½	120		80	15	14X14	F05 F07	Ø50 Ø70
50	2	140		87.5	15	14X14	F05 F07	Ø50 Ø70
65	2½	185		115	19	17X17	F07 F10	Ø70 Ø102
80	3	205		122	19	17X17	F07 F10	Ø70 Ø102
100	4	240		158	23	22X22	F10 F12	Ø102 Ø125